


**Instruction:**

- 1.Type:Film to Glass
- 2.Operating Voltage:≤10V
- 3.Response Time:≤10ms
- 4.Storage Temperature: -20℃~+70℃
- 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
- 6.Hitting Life:>1,000,000 Times ,250gf Force;
- 7.writing Life>100,000 Times 250gf Force;
- 8.Connect Material:FPC

- 9.Film Thickness:0.188mm
- 10.Glass Thickness:0.7mm
- 11.Light transmission: ≥78%
- 12.Force:100g or more
- 13.Linearity:≤1.5%
- 14.Insulation: ≥20MΩ
- 15.Resistance: X: 400Ω~700Ω  
Y: 200Ω~400Ω
- 16.Surface Hardness≥3H(pencil)

## Touch-Pane-VTW4035A0

### REVISIONS

| SCALE   | 1:1        | MATERIAL  | F/G      | Version  | 1.0    |
|---------|------------|-----------|----------|--|--------|
| UNIT    | mm         | TOLERANCE | ±0.3m    | NO.  | 1 of 1 |
| DESIGN  | Lucy       | DATE      | 20090615 |  <b>深圳市纬拓技术有限公司</b><br>Victor-Touch Technology Co., LTD.<br><small>TEL: 0755-6786080 FAX: 0755-6786080 www.victor-touch.com</small> |        |
| CHECK   | Peter · Li | DATE      | 20090615 |  |        |
| RELEASE | Victor     | DATE      | 20090615 |  |        |