


Instruction:

- 1.Type: Film to Glass
- 2.Operating Voltage: $\leq 10V$
- 3.Response Time: $\leq 10ms$
- 4.Storage Temperature: $-20^{\circ}C \sim +70^{\circ}C$
- 5.Operation Temperature/Humidity : $-10^{\circ}C \sim +60^{\circ}C / 20\% \sim 95\%$
- 6.Hitting Life: $> 1,000,000$ Times ,250gf Force;
- 7.writing Life $> 100,000$ Times 250gf Force;
- 8.Connect Material:FPC

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.1mm
- 11.Light transmission: $\geq 78\%$
- 12.Force: 100g or more
- 13.Linearity: $\leq 1.5\%$
- 14.Insulation: $\geq 20M \Omega$
- 15.Resistance: X: $410 \Omega \sim 750 \Omega$;
Y: $220 \Omega \sim 410 \Omega$.
- 16.Surface Hardness $\geq 3H$ (pencil)

Touch-Pane-VTW4056A0

REVISIONS

SCALE	1:1	MATERIAL	F/G	Version	A0
UNIT	mm	TOLERANCE	$\pm 0.3m$	NO.	1 of 1
DESIGN	Lucy	DATE	20090619	 深圳市伟拓光技术有限公司 Victor-Touch Technology Co., LTD. <small>0755-23222222 0755-2322222 www.victor-touch.com</small>	
CHECK	Peter • LI	DATE	20090619		
RELEASE	Victor	DATE	20090619		