



- Instruction:
- 1.Type:Film to Glass
 - 2.Operating Voltage: ≤10V
 - 3.Response Time: ≤10ms
 - 4.Storage Temperature: -20℃~+70℃
 - 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
 - 6.Hitting Life:>1,000,000 Times ,250gf Force;
 - 7.writing Life>100,000 Times 250gf Force;
 - 8.Connect Material:FPC

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.1mm
- 11.Light transmission: ≥78%
- 12.Force: 100g or more
- 13.Linearity: ≤1.5%
- 14.Insulation: ≥20M Ω
- 15.Resistance: Y: 220 Ω~410 Ω.
X: 410 Ω~750 Ω;
- 16.Surface Hardness ≥3H(pencil)

Touch-Pane-VTW4057A0

REVISIONS					
SCALE	1:1	MATERIAL	F/G	Version	A0
UNIT	mm	TOLERANCE	±0.3m	NO.	1 of 1
DESIGN	Lucy	DATE	20090505	深圳市伟拓光技术有限公司 Victor-Touch Technology Co., LTD. 0755-23222222 0755-23222222 www.victor-touch.com	
CHECK	Peter • LI	DATE	20090505		
RELEASE	Victor	DATE	20090505		