



Instruction:  
 1.Type:Film to Glass  
 2.Operating Voltage:≤10V  
 3.Response Time:≤10ms  
 4.Storage Temperature: -20℃~+70℃  
 5.Operation Temperature/Humidity: -10℃~+60℃/ 20%~95%  
 6.Hitting Life:>1,000,000 Times ,250gf Force;  
 7.writing Life>100,000 Times 250gf Force;  
 8.Connect Material:FPC

9.Film Thickness:0.188mm  
 10.Glass Thickness:1.1mm  
 11.Light transmission: ≥78%  
 12.Force:100g or more  
 13.Linearity:≤1.5%  
 14.Insulation: ≥20M Ω  
 15.Resistance: Y:180 Ω~330 Ω;  
 X:510 Ω~900 Ω.  
 16.Surface Hardness≥3H(pencil)

Touch-Pane-VTW4070A0					
REVISIONS					
SCALE	1:1	MATERIAL	F/A	Version	1.0
UNIT	mm	TOLERANCE	±0.05	NO.:	1 of 1
DESIGN	Lucy	DATE	20090520	深圳市纬拓光技术有限公司 Victor-Touch Technology Co., LTD.	
CHECK	Peter • Li	DATE	20090521		
RELEASE	Victor	DATE	20090521		