



由 Autodesk 教育版产品制作

Version	MARK	MODIFY	DATE

Instruction:
 1.Type:Film to Glass
 2.Operating Voltage:≤10V
 3.Response Time:≤10ms
 4.Storage Temperature: -20℃~+70℃
 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
 6.Hitting Life:>1,000,000 Times ,250gf Force;
 7.writing Life>100,000 Times250gf Force;
 8.Connect Material:FFC

9.Film Thickness: 0.188mm
 10.Glass Thickness: 0.7mm
 11.Light transmission: ≥75%
 12.Force: 100g or more
 13.Linearity: ≤1.5%
 14.Insulation: ≥20MΩ
 15.Resistance: Y: 150Ω~380Ω
 X: 510Ω~1100Ω
 16.Surface Hardness ≥3H(pencil)

Touch-Pane-VTW4070F3

REVISIONS

SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	±0.3mm	NO:	1 of 1
DESIGN	Lucy	DATE	20100810	深圳市伟拓光电技术有限公司 Victor-Touch Technology Co.,LTD.	
CHECK	Peter Li	DATE	20100810		
RELEASE	Victor	DATE	20100810		