


**Instruction:**

- 1.Type: Film to Glass
- 2.Operating Voltage:  $\leq 10V$
- 3.Response Time:  $\leq 10ms$
- 4.Storage Temperature:  $-20^{\circ}\sim +70^{\circ}$
- 5.Operation Temperature/Humidity :  $-10^{\circ}\sim +60^{\circ}/ 20\%\sim 95\%$
- 6.Hitting Life:  $>1,000,000$  Times ,250gf Force;
- 7.writing Life  $>100,000$  Times 250gf Force;
- 8.Connect Material: FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.1mm
- 11.Light transmission:  $\geq 78\%$
- 12.Force: 100g or more
- 13.Linearity:  $\leq 1.5\%$
- 14.Insulation:  $\geq 20M\Omega$
- 15.Resistance: X:  $410\Omega\sim 800\Omega$   
Y:  $200\Omega\sim 410\Omega$
- 16.Surface Hardness  $\geq 3H$ (pencil)

## Touch-Pane-VTW4080A3

### REVISIONS

SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	$\pm 0.3m$	NO.	1 of 1
DESIGN	Lacy	DATE	20090627	 <b>深圳市纬拓技术有限公司</b> Victor-Touch Technology Co., LTD. <small>TEL: 0755-2760888 FAX: 0755-2760888 www.victor-touch.com</small>	
CHECK	Peter • LI	DATE	20090627		
RELEASE	Victor	DATE	20090627		