


Instruction:

- 1.Type:Film to Glass
- 2.Operating Voltage: $\leq 10V$
- 3.Response Time: $\leq 10ms$
- 4.Storage Temperature: $-20^{\circ}\sim+70^{\circ}$
- 5.Operation Temperature/Humidity : $-10^{\circ}\sim+60^{\circ}/ 20\%\sim95\%$
- 6.Hitting Life: $>1,000,000$ Times ,250gf Force;
- 7.writing Life $>100,000$ Times 250gf Force;
- 8.Connect Material:FPC

- 9.Film Thickness:0.188mm
- 10.Glass Thickness:1.1mm
- 11.Light transmission: $\geq 78\%$
- 12.Force:100g or more
- 13.Linearity: $\leq 1.5\%$
- 14.Insulation: $\geq 20M\Omega$
- 15.Resistance: Y: 170 Ω ~330 Ω , X: 500 Ω ~950 Ω
- 16.Surface Hardness $\geq 3H$ (pencil)

Touch-Pane-VTW4102A1

REVISIONS

SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	$\pm 0.3m$	NO.	1 of 1
DESIGN	Lucy	DATE	20090618	 深圳市纬拓光技术有限公司 Victor-touch Technology Co., LTD. <small>TEL: 0755-4264000 FAX: 0755-4264000 www.victor-touch.com</small>	
CHECK	Peter • LI	DATE	20090618		
RELEASE	Victor	DATE	20090618		