



**Instruction:**

- 1.Type: Film to Glass
- 2.Operating Voltage: ≤10V
- 3.Response Time: ≤10ms
- 4.Storage Temperature: -20℃~+70℃
- 5.Operation Temperature/Humidity : -10℃~+60℃/ 20%~95%
- 6.Hitting Life:>10,000,000 Times ,250gf Force;
- 7.writing Life>1,000,000 Times 250gf Force;
- 8.Connect Material:FPC+PIN

- 9.Film Thickness: 0.188mm
- 10.Glass Thickness: 1.8mm
- 11.Light transmission: ≥78%
- 12.Force: 100g or more
- 13.Linearity: ≤5%
- 14.Insulation: ≥20M Ω
- 15.Resistance: 50Ω<PIN1, PIN2<280Ω  
50Ω<PIN2, PIN4<280Ω  
50Ω<PIN4, PIN6<280Ω  
50Ω<PIN6, PIN1<280Ω
- 16.Surface Hardness ≥3H(pencil)

**Touch-Pane-VTW5121A0**

REVISIONS					
SCALE	1:1	MATERIAL	F/G	Version	1.0
UNIT	mm	TOLERANCE	±0.3m	NO.	1 of 1
DESIGN	Luxey	DATE	20090610	 <b>深圳市沛拓技术有限公司</b> Viator-Touch Technology Co.,LTD. <small>0755-8999 8888 8888 www.viator-touch.com</small>	
CHECK	Peter • LI	DATE	20090611		
RELEASE	Viator	DATE	20090612		