


- Instruction:
- Type: Film to Glass
 - Operating Voltage: $\leq 10V$
 - Response Time: $\leq 10ms$
 - Storage Temperature: $-20^{\circ}C \sim +70^{\circ}C$
 - Operation Temperature/Humidity: $-10^{\circ}C \sim +60^{\circ}C / 20\% \sim 95\%$
 - Hitting Life: $> 10,000,000$ Times, $250gf$ Force;
 - writing Life: $> 1,000,000$ Times $250gf$ Force;
 - Connect Material: FPC+PIN

- Film Thickness: $0.188mm$
- Glass Thickness: $1.8mm$
- Light transmission: $\geq 75\%$
- Force: $100g$ or more
- Linearity: $\leq 5\%$
- Resistance: $50\Omega < PIN1, PIN2 < 250\Omega$
 $50\Omega < PIN3, PIN4 < 250\Omega$
 $50\Omega < PIN5, PIN6 < 250\Omega$
- Surface Hardness $\geq 3H$ (pencil)

Front ITO Film 0.188mm
 hard coating anti newton ring
 Back Glass—1.8mm

总厚度: 2.3 ± 0.15



Touch-Pane-VTW5191A0

REVISIONS

NO	DATE	REVISION	DESCRIPTION
1	20090506	1.0	Initial
2	20090506	1.1	Update

